

LED bulb GU10 7W 3000K 1000lm 170-250V

FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



LED type



The structural design of this product ensures effective heat dissipation.



Beam angle



Lamp type



Lifespan

Parameter	Value
Luminous efficacy	142 lm/W
Power	7 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1000 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Number of sockets (number of ropes)	Ceramic
Survival factor	0,9
Lifetime L70B50	30 000
Supply voltage range and voltage type	170-250 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Lamp's diameter	50
Beam angle	120 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000

Parameter	Value
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	55 mm
Master carton weight (kg)	7
EPREL ID	2 097 592
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	2
Total luminous flux (EPREL)	1 000
On-mode power P _{on} (EPREL)	7
Useful luminous flux Φ _{use} (EPREL)	1 000
Beam angle in degrees (EPREL)	120

Single packaging



Bulk packaging



Outer box quantity

100 pcs.

Europallet

