


Product code: 240119 EAN: 5901583240119

LED line® strip 150 SMD 12V blue 2,4W IP65



Product description

Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years. This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre. Manufacturer issues a 3-year warranty for this product.




	<p>Manufacturer issues a 3-year warranty for this product.</p>		<p>Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years.</p>
	<p>Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.</p>		<p>This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.</p>
	<p>Lifespan</p>		<p>Voltage range and voltage type</p>
			<p>Beam angle</p>
	<p>LED type</p>		<p>Compatible dimmer type</p>
	<p>Laminate (thickness)</p>		<p>LED quantity (1m)</p>
	<p>Cutting section</p>		<p>Type of adhesive tape</p>
	<p>Number of on/off cycles</p>		<p>Ambient temperature suitable for operation</p>
	<p>IEC protection class</p>		


Name of the parameter	Value
Colour of the light	Blue
Warranty (years)	3
Minimum purchase quantity	5
Lifetime L70B50	30000
Wattage (lm)	2,4 W
Wavelength	465nm
Current (Im)	0,2
Supply voltage range and voltage type	12 DC

Name of the parameter	Value
Metres per roll	5
The lumen maintenance factor	>0,7
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	30
Cutting section	10
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	YES
IEC protection class	III
LED strip (upper) IP protection rating	65
LED strip (bottom) IP protection rating	20
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	3 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	13,58
Product code	240119

Luminous [cd/klm]




Cumulative packaging



Number of pieces

100

Europallet



Number of pieces

960

Bulk quantity

24

Pallet height [mm]

984

Quantity in 1 layer

8

Number of layers

3