


Product code: 240232 EAN: 5901583240232

LED line® strip 300 SMD 12V yellow 4,8W



Product description

Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



IP protection rating



Lifespan



Voltage range and voltage type



LED type



Beam angle



SMD3528



Compatible dimmer type



Laminate (thickness)



LED quantity (1m)



Cutting section



Type of adhesive tape



Number of on/off cycles



Ambient temperature suitable for operation




IEC protection class

Name of the parameter	Value
Colour of the light	Yellow
IP protection rating	20
Warranty (years)	5
Minimum purchase quantity	5
Lifetime L70B50	50000
Wattage (lm)	4,8 W
Wavelength	590nm
Current (lm)	0,4
Supply voltage range and voltage type	12 DC

Name of the parameter	Value
Metres per roll	5
The lumen maintenance factor	>0,7
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	60
Cutting section	5
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	YES
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	2,5 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	3,9
Product code	240232

Luminous [cd/klm]



C0 - C180 **C90 - C270**

Cumulative packaging



Number of pieces	100
Width [mm]	340
Height [mm]	280
Length [mm]	440
Weight [kg]	0,1
Volume [m3]	0,042

Europallet



Number of pieces	2400
Bulk quantity	60
Weight [kg]	300
Weight [kg]	300
Pallet height [mm]	1800
Quantity in 1 layer	6
Number of layers	10