


Product code: 241505 EAN: 5901583241505



















LED line® strip 300 SMD 12V green 4,8W IP67



Product description

Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years. This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre. Manufacturer issues a 3-year warranty for this product.




	Manufacturer issues a 3-year warranty for this product.		Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years.
	Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.		This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.
	IP protection rating		Lifespan
	Voltage range and voltage type		
	Beam angle		LED type
	Compatible dimmer type		Laminate (thickness)
	LED quantity (1m)		Cutting section
	Type of adhesive tape		Number of on/off cycles
	Ambient temperature suitable for operation		IEC protection class

Name of the parameter	Value
Colour of the light	Green
IP protection rating	67
Warranty (years)	3
Minimum purchase quantity	5
Lifetime L70B50	30000
Wattage (lm)	4,8 W
Wavelength	520nm
Current (lm)	0,4
Supply voltage range and voltage type	12 DC

Name of the parameter	Value
Metres per roll	5
The lumen maintenance factor	>0,7
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	60
Cutting section	5
Type of adhesive tape	Piankowa
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor and outdoor use	YES
IEC protection class	III
Full box quantity	40 pc
Lamp's warm-up time to 60%	1
Width	10 mm
Height	5 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	12,04
Product code	241505


Cumulative packaging



Number of pieces

100

Europallet



Number of pieces

960

Bulk quantity

24

Pallet height [mm]

984

Quantity in 1 layer

8

Number of layers

3