



















**Technical sheet** 

MODUS P 7000 MULTI, 4600/5600/6600/7600lm, LED 840, 1500mm PC body + cover, IP66, cont. assembly 3x1,5mm

Code: P7000L4NDMULTI/P1 EAN: 8596099150181





## Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	7600
System power (W):	49	Luminaire efficacy (lm/W):	155
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP66
Color housing:	Grey	Impact strength:	IK08
Ball-proof:	Yes		
Suitable for suspended mounting:	Yes		
Material housing:	Plastic	Light source included:	Yes
Suitable for surface mounting:	Ves	Suitable for ceiling mounting:	Yes

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast

## Optical system

Optical system:	СО	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal

## **Dimensions**

Length (mm):	1500	Width (mm):	88
Height/depth (mm):	82	Weight (kg):	1,8
Electrical values			
Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220240
Control gear included:	Yes	Type of wiring:	Through wiring included
No dim function:	Yes		
Indoor use only:	Yes		