



NB3Q-TW01B

Touch screen HMI, 3.5 inch QVGA (320 x 240 pixel), TFT color, Ethernet + USB Host

Műszaki jellemzők

Screen diagonal	3.5 in
Number of pixels, horizontal	320
Number of pixels, vertical	240
Type of display	TFT
Frame colour	Black
Number of Ethernet ports	1
Number of USB ports	2
Number of RS-232 ports	1
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colours of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	129.8 mm
Height of the front	103.8 mm
Width of panel cutout	119 mm
Height of panel cutout	93 mm
Built-in depth	52.8 mm
Product Weight (unpacked)	490 g



CP1W-CN221

USB Programming cable, A-type male to B-type male, 1.8 m



NB3Q-KBA04

Accessory HMI, protective sheets for NB3Q (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

CAD Könyvtár



How to Import PLC Variables from Sysmac Studio

Gyakorlati útmutató

EN PDF 500 KB



Maxell CR-series button cells

Akkumulátorbiztonsági adatlap

EN PDF 100 KB



NB Faceplate 3.1 - Multilanguage

Szoftver

EN ZIP 80 MB



NB Series HMI Adatlap

HU PDF 1 MB



NB Series Programmable Terminal Brosúra

Brosúra

EN PDF 4 MB



NB-Designer Setup v1.5.3.1

Szoftver

EN ZIP 400 MB



NB-Series Kezdő lépések

EN PDF 10 MB



NB-Series Beállítás kézikönyv

EN PDF 6 MB



NB-Series Host Connection Beállítás kézikönyv

Beállítás kézikönyv

EN PDF 20 MB



NB-series Programmable Terminals (Europe) Kivonási megjegyzés

Kivonási megjegyzés

EN PDF 100 KB

A WEBOLDAL HASZNÁLATÁNAK FELTÉTELEI

Ez a PDF-dokumentum az OMRON európai ipari automatizálás weboldaláról lett létrehozva a következő időpontban: 15 October, 2024. Kattintson ide a [jogi nyilatkozat](#) eléréséhez.