



NB7W-TW01B

Touch screen HMI, 7 inch WVGA (800 x 480 pixel), TFT color, Ethernet + USB Host

Műszaki jellemzők

Screen diagonal	7 in
Number of pixels, horizontal	800
Number of pixels, vertical	480
Type of display	TFT
Frame colour	Black
Number of Ethernet ports	1
Number of USB ports	2
Number of RS-232 ports	2
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colours of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	202.0 mm
Height of the front	148 mm
Width of panel cutout	191 mm
Height of panel cutout	137 mm
Built-in depth	46 mm
Product Weight (unpacked)	1000 g



CP1W-CN221

USB Programming cable, A-type male to B-type male, 1.8 m



NB7W-KBA04

Protective sheets for NB7W (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

CAD Könyvtár



EVE CR-series button cells Akkumulátorbiztonsági adatlap

EN PDF 400 KB



How to Import PLC Variables from Sysmac Studio

Gyakorlati útmutató

EN PDF 500 KB



NB Faceplate 3.1 - Multilanguage

Szoftver

EN ZIP 80 MB



NB Series HMI Adatlap

HU PDF 1 MB



NB Series Programmable Terminal

Brosúra

EN PDF 4 MB



NB-Designer Setup v1.5.3.1

Szoftver

EN ZIP 400 MB



NB-Series Kezdő lépések

EN PDF 10 MB



NB-Series Beállítás kézikönyv

EN PDF 6 MB



NB-Series Host Connection

Beállítás kézikönyv

EN PDF 20 MB



NB-series Programmable Terminals (Europe) Kivonási megjegyzés

EN PDF 100 KB



NB7W-TW1_B HMIs Felhasználói kézikönyv

EN PDF 40 MB

A WEBOLDAL HASZNÁLATÁNAK FELTÉTELEI

Ez a PDF-dokumentum az OMRON európai ipari automatizálás weboldaláról lett létrehozva a következő időpontban: 15 October, 2024. Kattintson ide a [jogi nyilatkozat](#) eléréséhez.