

## ToLEDo Retro A60

ToLEDo RT GLS V3 CL 470LM 827 E27 SL

0027160



### Product features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- A++ energy rating - up to 118 lm/W
- Suitable for replacement of 40W incandescent lamps
- Gives same sparkling light effect as incandescent lamp
- 90% energy saving
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment friendly - no mercury and lower CO2 emissions
- Color temperature - 2700K Homelight



### NOTES

undefined

### PRODUCT OVERVIEW

IPC Code	0027160
Product name	ToLEDo RT GLS V3 CL 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	4.5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740283
E-number SE	8290503
Luminous flux (lm)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	300
Wattage (W)	4.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288271606

### DATA TABLE

#### General data

IPC Code	0027160
Product name	ToLEDo RT GLS V3 CL 470LM 827 E27 SL
Technology	LED

## ToLEDo Retro A60

ToLEDo RT GLS V3 CL 470LM 827 E27 SL  
0027160

Watt (Rated) (W)	4.5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality,Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740283
E-number SE	8290503

### Optical data

Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Beam Angle (°)	300
Beam angle (Rated) (°)	300
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	4.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	5
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Length (mm)	104
Nominal Product Diameter (mm)	60
Weight (kg)	0.029

### Packaging

Single packaging type	Carton
Product EAN number	5410288271606
Packaging single length / height (cm)	11.4

## ToLEDo Retro A60

*ToLEDo RT GLS V3 CL 470LM 827 E27 SL*

0027160

Packaging single width (cm)	6.4
Packaging single depth (cm)	6.4
DUN14 (inner)	25410288271600
Units per inner package	6
Packaging inner length / height (cm)	19.9
Packaging inner width (cm)	13.7
Packaging inner depth (cm)	12.9
DUN14 (outer)	15410288271603
Units per outer package	60
Packaging outer length / height (cm)	72.0
Packaging outer width (cm)	43.0
Packaging outer depth (cm)	15.8

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

## ToLEDo Retro A60

ToLEDo RT GLS V3 CL 470LM 827 E27 SL

0027160

