



Click here to discover this product in 360°

# PRODUCT INFORMATION

Reference : FD-020-227

Protocols: 2 wires





Technologies: Mifare Plus, Mifare Classic, Desfire, BLE

## DESCRIPTION

The Alpha reader is a 2-SMART range reader specially developed for our iPassan access controllers and Easy Door Controller.

This reader is based on FDI 2-wire protocol that delivers exclusive security and features to it.

When this reader is combined with iPassan, it can manage BLE (Bluetooth Low Energy) access, which lets users authenticate via their Android or iOS mobile phone app.

It is designed to integrate the Urmet Alpha modular door entry panel system.

## KEY CHARACTERISTICS

- Reader compatible with FDI Mifare® Classic and Mifare® Plus (AES 128 bit encryption)
- Enhanced security and easy to install with its 2-wire output and encrypted bus
- · Integrated LEDs and buzzer
- Firmware can be updated remotely if required

#### Power supply

The Alpha reader draws its power supply from the FDI access controller.

#### Communication

The 2-SMART reader two-way communicates permanently (FDI protocol) with the iPassan controller or the Easy Door Controller, via its 2-wire bus. As such, the controller is real-time aware if the reader is correctly linked and displays the status via a LED on the controller and on the monitoring screen (iPassan)

#### **Updating firmware**

2-SMART Alpha reader firmware can be updated via iPassan Manager software.



## TECHNICAL CHARACTERISTICS

## Power supply

Operating voltage: 12V supplied by the controller via the 2 wires

## Outputs

• 2-SMART output: 2-wire

• Max. cable length: 100 metres

• Frequency: 13.56 MHz (Mifare® Classic and Mifare® Plus)

#### Read distance

- Mifare® Classic: up to 30 mm depending on the key/pass
- Mifare® Plus: up to 20 mm depending on the key/pass
- Bluetooth: up to 15 m depending on the smartphone, the type of access used and the reader and app settings

### **LEDs**

- 3 colors: blue, red and green.
- Behaviour adjustable via iPassan Manager

## **Temperature**

• Operating: -20°C to 50°C

• Storage temperature: -20°C to 70°C

• Humidity: 85 RH max

#### Size

Size (L x I x H): 125 mm x 90 mm x 26 mm

• Weight: 150g



# **COMPLEMENTARY ASSOCIATED PRODUCTS**

• <u>FD-020-227</u> : Alpha reader