Safe-Torque torque wrenches







| EAN: | 4013288223043 | Size: | 275x100x65 mm |
|-----------------|-----------------------|---------------------------|---------------|
| Part number: | 05075832001 | Weight: | 1070 g |
| Article number: | Safe-Torque A 2 Set 1 | Country of origin: | CZ |
| | | Customs tariff number: | 82079030 |

- Slip-over release mechanism the set torque can never be overtightened
- Torque Lock function: The torque function can be deactivated and the tool can then be used as a standard ratchet with high loosening moments and for applications with defined angles of rotation
- For controlled clockwise and counterclockwise torque operation tightening and loosening with or without torque
- Easy setting and saving of the desired torque value with audible and tactile clicks when reaching the scale values
- After the target torque has been reached, the release angle is only 30°
- The fine toothing with 72 teeth allows for a low return angle of 5°
- 1/4" hexagon drive for the use of 1/4" bits
- Use of 1/4" sockets also possible with the Wera adaptor 870/1

23-piece set; in surface-friendly, compact and extremely robust textile box. Small size and low weight for better mobility. 1 Safe-Torque A 2 torque wrench with 1/4" hexagonal drive, measuring range 2-12 Nm; for controlled clockwise and counterclockwise torque operation; tightening and loosening with or without torque, disengageable torque function (Torque Lock function); 72 teeth; low return angle of 5°; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached, slip-over release mechanism when the set torque is reached; ergonomic 2-component handle; 9 Zyklop sockets, 12 bits (1/4", 50 mm long), one connector for sockets (1/4" external hexagon to 1/4" external square head).



LOCK


Safe-Torque torque wrenches





Safe-Torque

Slide-over mechanism prevents application of excessive torques



The Safe-Torque A2 torque wrench is equipped with a slideover mechanism. Once the set torque has been reached, the tool cannot be overtightened, so that excessive torque cannot be applied.

Low return angle

Torque Lock function



The torque function can be deactivated. The Safe-Torque torque wrench can then also be used as a standard ratchet with high loosening moments and for applications with defined angles of rotation.


For 1/4" bits

For clockwise and counterclockwise operation



The Safe-Torque torque wrench is suitable for clockwise and counterclockwise operation with a set torque. When the Torque Lock function is deactivated, tightening and loosening is enabled without torque.

Adapter for 1/4" sockets





Easy setting and saving of the required torque with audible and tactile clicks on reaching the scale values.



The fine-toothed Safe-Torque torque wrench with 72 teeth has a back-pivoting angle of only 5°. The small stroke offers quick and precise working in all installation positions.



The Safe-Torque A 2 torque wrench has a $\frac{1}{4}$ " bit mounting with a strong permanent magnet and is suitable for bits with $\frac{1}{4}$ " external hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3 and Wera connection series 1 and 4.



With the 870/1 connector (1/4" external hexagon to 1/4" external square head) the Safe-Torque A 2 can also be used with 1/4" sockets.

Safe-Torque torque wrenches

Set contents:

| Safe-Torque A 2 torque wi | rench with 1/4" hexagon d 05075801001 | | 2-12 Nm, 2-12 Nm 2-12 Nm | |
|-----------------------------------------------|------------------------------------------|----------|------------------------------------|--|
| | 00070001001 | 17 | | |
| 8790 HMA Zyklop 1/4" socket, 5.5 x 23 mm | | | | |
| | 05003504001 | 1x | ••• | |
| | 05003505001 | 1x | | |
| | 05003506001 | | 7 x 23 mm | |
| Me 2 | 05003507001 | 1x | | |
| | 05003508001 | 1x | • · · = • · · · · · | |
| | 05003509001 | 1x | | |
| | 05003510001 | 1x | 11 x 23 mm | |
| | 05003511001 | 1x | 12 x 23 mm | |
| | 05003512001 | 1x | 13 x 23 mm | |
| 870/1 Adaptor, 1/4" x 25 mm | | | | |
| 0 | 05136000001 ¹⁾ | 1x | 1/4" x 25 mm | |
| | 1) With friction ball; for manual nut sp | inner so | ckets | |
| Wera | | | | |
| 851/4 Z bits, PH 2 x 50 mm | n | | | |
| \mathbf{O} | | 1x | PH 2 x 50 mm | |
| | | | | |
| 867/4 Z TORX® bits, TX 10 | | | | |
| \mathbf{O} | 05060132001 | | TX 10 x 50 mm | |
| di Werg | 05060133001 | | TX 15 x 50 mm | |
| | 05060134001 | 1x | | |
| | 05060135001 | 1x | | |
| | 05060136001 | 1x | | |
| | 05060137001 | 1x | TX 30 x 50 mm | |
| 840/4 Z bits, 2.5 x 50 mm | | | | |
| 0 | 05059604001 | 1x | 2.5 x 50 mm | |
| M Werca | 05059605001 | 1x | 3 x 50 mm | |
| | 05059610001 | 1x | 4 x 50 mm | |
| | 05059615001 | 1x | 5 x 50 mm | |
| | 050596200011) | 1x | 6 x 50 mm | |
| | 1) Hexagonal blade | | | |
| Hook and Loop Fastener Strip 240, 50 x 240 mm | | | | |
| | | 1x | 50 x 240 mm | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

