

Product description

Model with monitoring contact as potential-free changeover contact, actuated by the latch bolt.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Compatible with available striking plates
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Note

- Not an authorised locking system for doors along escape and rescue routes

Technical data

Handing	Universal
potential	12 V DC
Noise damped	Yes
Adjustable latch (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Fail-unlocked	Yes
Rated operating voltage tolerance range	± 10 %
Rated resistance	51 Ohm
Switching capacity - monitoring contact	24 V / 1 A
Current consumption 12 V DC	235 mA
Break-in resistance	3750 N
Height	74 mm
Width	16 mm
Depth	26 mm
Max. latch preload DC (stabilised)	30 N
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000
Suitable for fire doors	No

Article number 138RR- - - - - E91

EAN-Number 4042203342989

